

Container Dimensions

Dry Containers	Scale	External Dimensions			Door Opening		Internal Dimensions			Weight			Volume
		Length	Width	Height	Width	Height	Length	Width	Height	Max Gross	Tare	Payload	
20 GP	Metric	6.096	2.438	2.591	2.340	2.274	5.896	2.350	2.393	30.480	2.280	28.200	33.000
	Feet	20.000	8.000	8.500	7' 8.06"	7' 5.5"	19' 4.06"	7' 8.5"	7' 9.87"	67.200	5.030	62.170	1179.000
40 GP	Metric	12.192	2.438	2.591	2.340	2.274	12.032	2.350	2.393	32.500	3.700	28.800	67.000
	Feet	40.000	8.000	8.500	7' 8.06"	7' 5.5"	39' 5.81"	7' 8.5"	7' 10.18"	71.650	8.157	64.493	2.390
40 HU	Metric	12.192	2.438	2.926	2.340	2.577	12.032	2.350	2.697	32.500	3.800	28.620	76
	Feet	40.000	8.000	9.600	7' 8.06"	8' 5.4"	39' 5.81"	7' 8.5"	8' 10.18"	71.650	8.550	63.100	2.700
45 HU (Aluminium)	Metric	7.620	2.438	2.926	2.340	2.584	13.582	2.347	2.696	32.500	3.900	28.600	86
	Feet	45.000	8.000	9.600	7' 8.06"	8' 5.68"	44' 6.68"	7' 8.38"	8' 10.12"	71.650	8.600	63.050	3.071
45 HU (Steel)	Metric	7.620	2.438	2.926	13.556	2.352	13.556	2.352	2.697	32.500	4.900	27.600	86
	Feet	45.000	8.000	9.600	7' 8.38"	8' 5.75"	44' 5.68"	7' 8.56"	8' 10.18"	71.650	10.800	60.850	3.040
Reefer Containers													
40 RF	Metric	12.192	2.438	2.926	2.278	2.473	11.578	2.280	2.425	34.000	4.200	29.800	64.000
	Feet	40.000	8.000	9.600	7' 5.68"	8' 1.31"	37' 11.81"	7' 5.75"	7' 11.43"	74.597	9.425	65.532	2.261
Flat Racks													
Flat Racks	Scale	External Dimensions			Length Between		Max	Weight			Volume		
		Length	Width	Height	Headers	Cnrn Posts		Width	Max Gross	Tare		Payload	
20 FR Fixed Corner	Metric	5.935	2.398	2.327	5.935	5.693	2.106			24.000	2.560	21.440	
	Feet	19' 5.62"	7' 10.37"	7' 7.56"	19' 5.62"	18' 8.12"	6' 10.87"			52.911	5.644	47.267	
20 FR Collapsible	Metric	5.966	2.418	2.286	5.850	5.422	2.058			30.480	2.970	27.510	
	Feet	19' 6.81"	7' 11.81"	7' 6"	19' 2.31"	17' 9.43"	6' 9"			67.194	6.547	60.647	
40 FR Fixed Corner	Metric	12.080	2.438	2.103	12.080	11.796	2.114			30.480	5.480	25.000	
	Feet	39' 7.56"	8' 6' 10.81"	39' 7.56"	38' 8.37"	6' 11.18"			67.197	12.081	55.116		
40 FR Open Ended	Metric	12.192	2.230	1.986	11.900	11.710	2.178			45.000	4.500	40.500	
	Feet	40'	7' 3.75"	6' 6.37"	39' 0.5"	38' 5"	7' 1.69"			99.208	9.921	89.287	
40 FR Flush Fold	Metric	12.178	2.365	1.943	12.058	11.662	2.224			45.000	5.200	39.800	
	Feet	39' 11.43"	7' 9.16"	6' 4.43"	39' 6.68"	38" 3.12"	7' 3.5"			99.208	11.464	87.744	
Open Tops													
Open Tops	Scale	External Dimensions			Door Opening		Top Opening		Weight			Volume	
		Length	Width	Height	Width	Height	Length	Width	Max Gross	Tare	Payload		
20 OT (Aluminium)	Metric	5.919	2.340	2.286	2.286	2.251	5.425	2.223		24.000	2.177	21.823	32.000
	Feet	19' 5"	7' 8.16"	7' 6"	7' 6"	7' 9.56"	7' 3.56"	7' 3.5"		52.909	4.799	48.110	1.143
20 OT (Steel)	Metric	5.893	2.346	2.353	2.338	2.273	5.488	2.230		30.480	2.250	28.230	32.000
	Feet	19' 3.93"	7' 8.31"	7' 8.56"	7' 8"	7' 5.5"	18'	7' 3.75"		67.194	4.960	62.234	1.143
40 OT (Aluminium)	Metric	12.043	2.338	2.272	2.289	2.253	11.662	2.162		30.480	4.300	26.180	64.000
	Feet	39' 6.06"	7' 8"	7' 5.43"	7' 6.06"	7' 4.68"	38' 1.5"	7' 1.16"		67.197	9.480	57.717	2.286
40 OT (Steel)	Metric	12.029	2.348	2.359	2.338	2.275	11.662	2.188		32.500	3.800	28.700	66.000
	Feet	39' 5.56"	7' 8.37"	7' 8.81"	7' 8"	7' 5.56"	38' 1.5"	7' 2.12"		71.650	8.378	53.273	2.355